

GDPA Fasteners

Near Railway godowns, Jalandhar, (Pb.) India www.qdpaindia.com

	DECLARATION OF PERFORMANCE (DOP)				
1	PRODUCT SIZE	M-16	REF NO.	GD-BNW-16Z(01)-072013	
2	PRODUCT GRADE	8.8	Finish	EZP	
3	PRODUCT TYPE	Non Preloading Structural Bolting Assembly			
4	PRODUCT REFERENCE STANDARD	EN 15048-Part 1 and 2			
5	INTENDED USE	General engineering and structures			
6	MANUFACTURER	GDPA Fasteners, India			
7	ADDRESS OF MANUFACTURER	Near Railway godowns Jalandhar City (144004) - Punjab -India			
8	CONTACT NO. OF MANUFACTURER	(+91) 0181-2642003, 0181-2642006			
9	NAME AND IDENTIFICATION OF NOTIFYING BODY	TUV Nord Systems, GmbH & Co. KG - (0045)			
10	PRODUCT DESCRIPTION	HEX SCREWS ISO 4017-8.8, HEX NUTS ISO 4032-CL-10, WASHER ISO 7091-100HV			
11	FACTORY PRODUCTION CONTROL CERTIFICATE NO.	CE-0045 -CPD -1536			
12	AUTHORIZED REPRESENTATIVE	Mr. Emanuel Masih.			
DECLADATION DEDECOMANCE					

DECLARATION PERFORMANCE

DECEMBATION I EM OMINANCE				
Essential Characteristics	Performance	Harmonized Specification		
Bolts		<u>-</u>		
Tensile strength	min.800 MPa	EN 15048-part 1&2		
Stress at 0.2% non proportional elongation	min.640 MPa			
Stress under proof load	min.580 MPa			
Strength under wedge loading	min.130 KN			
Hardness(Rockwell)	min.22 Hrc			
Impact Strength	Minimum 27 J at -20 degrees C			
Release of dangerous substances	less than 0.2 ppm			
Durability (corrosion protection)	Min. coating thickness 5 Microns			
Nuts				
Proof Load	Min. 164.9kn			
Hardness	min.26 Hrc			
Release of dangerous substances	less than 0.2 ppm			
Durability (corrosion protection)	Min. coating thickness 5 Microns			
Washers				
Hardness(Rockwell)	Minimum 100 HV			
Release of dangerous substances	less than 0.2 ppm			
Durability (corrosion protection)	Min. coating thickness 5 Microns			
Assemblies				
Tensile resistance of the assembly	min.130 KN			
Durability (corrosion protection)	Min. coating thickness 5 Microns			

The performance of the product identified in point 1&2 in confirmity with the declared performance in point 12. This declaration of performance is used under the sole responsibility of the manufacturer identified in point 7. Signed for and on behalf of the manufacturer by.

Emanuel Masih (Head Quality Assurance) GDPA Fasteners, (Jalandhar)India Dated 01-07-2013